

ND1103

24ℓ pneumatic mobile oil dispenser - distr. pneumatico carrellato da 24ℓ - distributeur pneumatique mobile de 24ℓ



This device allows new oil transfer by putting under pressure, through inflator inlet, a 24ℓ tank equipped with 2m delivery hose and nozzle. The tank is equipped with an overpressure valve (max 8bar), a pressure gauge to keep monitored pressure inside, while the oil level can be easily checked through a visual level indicator on the side of the tank.




Questo dispositivo permette il travaso di olio nuovo attraverso la messa in pressione tramite attacco gonfiagomme di un serbatoio carrellato da 24ℓ e permette l'erogazione tramite un tubo di mandata di 2m e una pistola di erogazione. Il serbatoio è dotato di una valvola di sovrappressione (max 8bar) e di un manometro per monitorare la pressione all'interno del serbatoio, mentre il livello dell'olio è facilmente osservabile tramite indicatore di livello visivo laterale.



Ce dispositif vous permet d'avoir un réservoir de transfert d'huile avec un tuyau de livraison de 2m et pistolet de distribution. Le réservoir est équipé d'une vanne se surpression (max 8bar), d'un manomètre; le niveau d'huile peut être vérifié à l'aide d'un indicateur de niveau sur le côté du réservoir.

datasheet

tank capacity capacità serbatoio capacité réservoir	24ℓ
max working pressure pressione max di lavoro pression max de travail	8 bar
nominal flow rate portata nominale débit nominal	16 ℓ/min
air inlet connection raccordo ingresso aria raccordement entrée d'air	1/4" inflator inlet 1/4" attacco gonfiagomme 1/4" valve de gonflage
delivery hose lunghezza tubo di mandata longueur tuyau	2m



330x340x770 mm



10.0 kg

EN - do not dispense brake fluid, fuels and aggressive liquids.

IT - non distribuire liquido freni, carburanti e liquidi corrosivi.

FR - ne pas utiliser liquide de frein, carburants ou liquides corrosifs